










1. ELECTRICAL CHARACTERISTICS:
- 1.1 CONTACT RESISTANCE: $40\text{m}\Omega$ Max FOR INITIAL. $10\text{m}\Omega$ CHANGE AFTER TEST.
MEASURE AT 20mV , $100\mu\text{A}$.
 - 1.2 CONTACT CURRENT RATING: 5A FOR COLLECTIVELY POWER SUPPLY
PIN(PIN1, A4, A9, A12, B1, B4, B9, B12) ; 1.25A FOR VCONN PIN; 0.25A FOR OTHER
SIGNAL PIN.
 - 1.3 DIELECTRIC WITHSTANDING VOLTAGE: 100V AC R.M.S.
 - 1.4 INSULATION RESISTANCE $100\text{M}\Omega$ Min
 - 1.5 OPERATING TEMPERATURE: $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
- 2 MECHANICAL CHARACTERISTICS:
- 2.1 MATING FORCE: $5 \sim 20\text{ N}$.
 - 2.2 UNMATED FORCE: $8 \sim 20\text{ N}$ INITIAL TEST; $6 \sim 20\text{ N}$ DURABILITY AFTER TEST
 - 2.3 DURABILITY: 10,000 CYCLES

USB TYPE-C FULL-FEATURED RECEPTACLE INTERFACE PIN ASSIGNMENTS

PIN	Signal Name	Description	PIN	Signal Name	Description
A1	GND	Ground return	B12	GND	Ground return
A2	SSTXp1	Positive half of first SuperSpeed TX differential pair	B11	SSRXp1	Positive half of first SuperSpeed RX differential pair
A3	SSTXn1	Negative half of first SuperSpeed TX differential pair	B10	SSRXn1	Negative half of first SuperSpeed RX differential pair
A4	VBUS	Bus Power	B9	VBUS	Bus Power
A5	CC1	Configuration Channel	B8	SBU2	Sideband Use (SBU)
A6	Dp1	Positive half of the USB 2.0 differential pair-Position 1	B7	Dn2	Negative half of the USB 2.0 differential pair-Position 2
A7	Dn1	Negative half of the USB 2.0 differential pair-Position 1	B6	Dp2	Positive half of the USB 2.0 differential pair-Position 2
A8	SBU1	Sideband Use (SBU)	B5	CC2	Configuraation Channel
A9	VBUS	Bus Power	B4	VBUS	Bus Power
A10	SSRXn2	Negative half of second SuperSpeed RX differential pair	B3	SSTXn2	Negative half of second SuperSpeed TX differential pair
A11	SSRXp2	Positive half of second SuperSpeed RX differential pair	B2	SSTXp2	Positive half of second SuperSpeed TX differential pair
A12	GND	Ground return	B1	GND	Ground return

GENERAL TOLERANCES		UNIT	mm		
DISTANCE	X.	MATERIAL		SEE NOTES	
	X. ±0.25	FINISHED		SEE NOTES	
	.X ±0.20	APPROVED		KATE DENG	
	.XX ±0.15	CHECKED		KATE DENG	
	.XXX ±0.10	DESIGN		FAND	
ANGLE		DRAWN		Wang Yan	
	X. ±3.0°				
	.X ±2.0°				
	.XX ±1.0°				



杰康富精密电子有限公司
JKF precision Electronics Co., LTD

TITLE:

TYPE C/F 24PIN 防水IP68板上双贴 SMT


PART NO.

JK-US4024AGB0042R-1




DRAWING NO.

SIZE	A4	SHEET	1 OF 1	REV.	A
------	----	-------	--------	------	---


REV.	ECN NO.	DESCRIPTION	DRAW/DATE	CHECKED	APPROVED
------	---------	-------------	-----------	---------	----------



RECOMMENDED PCB LAYOUT
(Tolerance=±0.05)



SECTION A-A
PANEL CUT-OUT REFERENCE



说明:






1. Colplanarity: 0.08最大红外线前., 0.10mm MAX
2. 舌PIN的位置:IR前 : 0.08mm MAX; IR 后0.12mm MAX;
3. P/N:
4. 包装方式 : 载带包装
5. 接触区和焊接区无毛刺, 除特说明, 冲压毛刺为0.05mm MAX.
6. 未标注尺寸公差为依自由公差为准.
7. 成品端子平面度必须100%检测.
8. 成品可靠性测试要求参照规格书.
9. 产品满足 ROHS 2.0

9	密封圈	1PCS	硅胶, 黑色	
8	胶水	1PCS	环氧胶, 黑色	
7	外壳	1PCS	SUS304 ,T=0.15. 镀镍50u" MIN.	
6	内拉伸壳	1PCS	SUS304,T=0.20.	
5	EMI拉伸壳	1PCS	SUS304 ,T=0.12. 镀镍50u" MIN.	
4	上排端子	1SET	C18400,T=0.12. 底层镀镍 50-100u",功能接触区单面	
3	下排端子	1SET	刷镀 Au 15u",焊接区双面镀金 G/F.	
2	中板	1PCS	SUS301-1/4 H, 镀镍50u" MIN.	
1	塑胶	1PCS	PA46 BLACK	
项目	组成部件	用量	材质/处理	备注


GENERAL TOLERANCES		UNIT	mm
DISTANCE	X.	±0.25	
	.X	±0.20	
	.XX	±0.15	
	.XXX	±0.10	
ANGLE	X.	±3.0°	
	.X	±2.0°	
	.XX	±1.0°	

杰康富精密电子有限公司	
J K F precision Electronics Co., LTD	
TITLE:	TYPE C/F 24PIN 防水IP68板上双贴 SMT
PART NO.	JK-US4024AGB0042R-1
DRAWING NO.	
SCALE	1:1
SIZE	A4
SHEET	1 OF 1
REV.	A

REV.	ECN NO.	DESCRIPTION	DRAW/DATE	CHECKED	APPROVED
------	---------	-------------	-----------	---------	----------



每盘真空包装+干燥剂



	REEL	CARTON
CONNECTOR (PCS)	800	8800

GENERAL TOLERANCES		UNIT	mm			 杰康富精密电子有限公司 J K F precision Electronics Co., LTD	
DISTANCE	X.	±0.25		MATERIAL	SEE NOTES		
	.X	±0.20		FINISHED	SEE NOTES	TITLE:	
	.XX	±0.15		APPROCED	KATE DENG	TYPE C/F 24PIN 防水IP68板上双贴 SMT	
	.XXX	±0.10		CHECKED	KATE DENG	PART NO.	
ANGLE	X.	±3.0°		DESIGN	FAND	DRAWING NO.	
	.X	±2.0°		DRAWN	Wang Yan	JK-US4024AGB0042R-1	
	.XX	±1.0°				SCALE	1:1
						SIZE	A4
						SHEET	1 OF 1
						REV.	A

REV.	ECN NO.	DESCRIPTION	DRAW/DATE	CHECKED	APPROVED
Frame_A4	9	8	7	6	5