








PIN ASSIGNMENT							
A1	A4	A5	A6	A7	A8	A9	A12
GND	VBUS	CC1	DP1	DN1	SBU1	VBUS	GND
GND	VBUS	SBU2	DN2	DP2	CC2	VBUS	GND
B12	B9	B8	B7	B6	B5	B4	B1

- 一. 原材料:
1. 塑胶:UL 94V-0型LCP黑色
2. 端子:0.15厚铜合金 C7025
3. 外壳:不锈钢 304
4. 卡勾:不锈钢 301
- 二. 电镀:
1. 端子:半金镀1u"
2. 外壳:镀哑镍
- 三. 机械性能:
插入力:5~20N
拔出力:寿命测试前8~20N,
寿命测试后5~20N
耐插拔:500次/H, 10000 次
工作温度:-30℃~+80℃
储存温度:-20℃~60℃
- 四. 电气性能:
额定电流: 5A
接触阻抗:寿命测试前40 mΩ Max.
寿命测试后50 mΩ Max
耐高压:100V AC 1分钟 Min.
无击穿, 无电弧
绝缘阻抗:100 MΩ Min.
- 五. 环境性能:
环 保: 产品符合ROHS要求
盐雾测试: 温度35±2℃,
湿度: 95~98%;
PH值: 6.5~7.2,
镀金区48H, 镀镍区24H
- 六. 焊接工艺: 推荐使用回流焊
本产品耐温260度, 8S



5	OUTER SHELL	SUS304 T=0.25mm	NI 40u"MIN	1 PCS
4	INNER SHELL	SUS304 T=0.30mm	NI 40u"MIN	1 PCS
3	SHIELDING PLATE	SUS304 T=0.15mm	N/A	1 PCS
2	CONTACT	C7025 T=0.15mm	Mating area 1u"Au Solder Tails:G/F Underplate:50u"Min Ni overall	2 SET
1	INSERT MOLDING	LCP UL94V-0	BLACK	1 PCS
NO.	DESCRIPTION	MATERIAL	REMARKS	

GENERAL TOLERANCES		UNIT	mm
DISTANCE	X.	±0.25	
	.X	±0.20	
	.XX	±0.15	
	.XXX	±0.10	
ANGLE	X.	±3.0°	
	.X	±2.0°	
	.XX	±1.0°	


杰康富精密电子有限公司
J K F precision Electronics Co. LTD

TITLE: TYPE-C 母 16P 板上 垫高 4.3 (中心高5.9)

PART NO. JK-US7716AGB00215R

DRAWING NO.


SCALE 1:1 SIZE A4 SHEET 1 OF 2 REV. A



NOTES

1. 帶子引導長度

LEAD TAPE LENGTH



2. 上帶 剝離力為: 0.1~1.3N(10.2gf~130gf)


PEELING OFF FORCE OF TOP TAPE: 0.1~1.3N(10.2gf~130gf)

出貨'運輸過程中一定注意:

THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT:


卷帶在運輸過程中不能散開

PEELING OFF SHOULD NOT BE ALLOWED DURING TRANSPORTATION



TAPE & REEL


1 REEL
= 500 PCS



BOX

DIMENSIONS:
34.0X34.0X23.0

LABEL



1 CARTON
=10 REELS
=5000 PCS

包裝明細表 (The detail of the packing) Carton						
產品料號 (Product No.)	包裝容量 (Packing Capacity)			重量 Weight (Kg)		
	pcs/box	boxs/Carton	Pcs/Box	N.W./Pcs	N.W./Box	G.W./Box
JK-US7716AGB00215R	500	10	5000	----	----	----

REV.	ECN NO.	DESCRIPTION	DRAW/DATE	CHECKED	APPROVED

Frame_A4
Rev.A2013/09/10

9

8

7

6

5

4

3

2

1

GENERAL TOLERANCES		UNIT	mm		
DISTANCE	X.	±0.25		MATERIAL	SEE NOTES
	.X	±0.20		FINISHED	SEE NOTES
	.XX	±0.15		APPROCD	KATE DENG
	.XXX	±0.10		CHECKED	KATE DENG
ANGLE	X.	±3.0°		DESIGN	FAND
	.X	±2.0°		DRAWN	Wang Yan
	.XX	±1.0°			

杰康富精密电子有限公司 J K F precision Electronics Co. LTD		TITLE:		TYPE-C 母 16P 板上 垫高 4.3 (中心高5.9)	
		PART NO.		JK-US7716AGB00215R	
		DRAWING NO.			
SCALE	1:1	SIZE	A4	SHEET	2 OF 2
REV.	A				

F

E

D

C

B

A